

# Product Specifications



		FaceStation 2	BioStation 2	BioEntry W2	BioEntry P2	BioLite N2	BioMini 2
Core Functions	Product Code	BC-FSA (multiCLASS), BC-FSD (EM)	BC-BSI (iCLASS SE), BC-BSH (Prox), BC-BSM (Mifare), BC-BSE (EM)	BC-BWA (multiCLASS), BC-BWH (Prox), BC-BWD (EM)	BC-BPD (EM), BC-BPA (multiCLASS)	BC-BNA (multiCLASS), BC-BND (Mifare)	BIOMINI2
	Application	Access Control	Access Control	Access Control	Access Control	Access Control	Enrollment
	Authentication	Facial/Pin/Card	Finger/Card/Pin	Finger/Card	Finger/Card	Finger/Card/Pin	-
	Card Options	125 KHz EM, 13.56Mhz: MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, NFC, 2.4GHz BLE 13.56 MHz iClass SE/ SEOS	125 KHz EM, 125KHz Prox, 13.56 MHz Mifare, 13.56 MHz iClass SE/ SEOS	125 KHz EM, 125KHz Prox, 13.56 MHz Mifare, 13.56 MHz iClass SE/ SEOS	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1, FeliCa, NFC, 13.56 MHz iClass SE/ SEOS	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire/EV1 & 2.4GHz BLE, 13.56 MHz iClass SE/ SEOS	-
Capacity	Template Capacity	30,000 (1:1), 3,000 (1:N)	500,000 (1:1), 20,000 (1:N)	500,000 (1:1), 200,000 (1:N)	10,000 (1:1), 10,000 (1:N)	10,000 (1:1), 10,000 (1:N)	-
	Log Capacity	5,000,000 (text), 50,000 (image)	3,000,000 (text)	1,000,000 (text)	1,000,000 (text)	1,000,000 (text)	-
Interfaces	TCP/IP	Yes	Yes	Yes	Yes	Yes	-
	RS485/ OSDP	1ch Host or Slave (Selectable)	2 Channels	1ch Host or Slave (Selectable)	1ch Host or Slave (Selectable)	1ch Host or Slave (Selectable)	-
	Weigand	1ch Input, 1ch Output	1ch Input, 1ch Output	1ch Input or Output (Selectable)	1ch Input or Output (Selectable)	1ch Input or Output (Selectable)	-
Hardware	CPU	1.4 GHz Quad Core	1.0 GHz Single Core	1.2 GHz Quad Core	1.0GHz	1.2 GHz	-
	Memory	8GB Flash + 1GB RAM	8GB Flash + 256MB RAM	2GB Flash + 256MB RAM	8GB Flash + 64MB RAM	4GB Flash + 64MB RAM	-
	LCD	4 Colour TFT	840px Graphic LCD	-	-	1.77" Color LCD	-
	LED Indicator	-	Multi Color LED	Multi Color LED	Multi Color LED	-	-
	IP Rating	-	IP65 (Dust & Water Protection)	IP67, IK09	-	IP67 (Dust & Water Protection)	-
	Tamper	Supported	Supported	Supported	Supported	Supported	-
	POE	Not Supported	Supported	Supported	Not Supported	Not Supported	-
	Operating Voltage	24V DC	12V DC	12V DC	12V DC	12V DC	-
	Operating Current	2.5 A	1.5 A	1 A	1 A	1.5 A	-
	Operating Temperature	-20-50°C	-20-50°C	-20-50°C	-20-50°C	-20-50°C	-20-50°C
Dimensions	141 x 164 x 125mm	142.24 x 144.78 x 45.72mm	50.8 x 172.72 x 43.18 mm	50 x 164 x 37.5mm	58 x 190 x 44 mm	66 x 90 x 58 mm	
BioConnect Enterprise		<b>Feature</b>	<b>Max. Devices</b>	<b>Synchronized User Database</b>	<b>Recommended Users</b>	<b>Suprema V1 Hardware</b>	<b>Suprema V2 Hardware</b>
	Basic	BC-BSC	20	Yes	> 50	Yes	Yes
	Standard	BC-STND	50	Yes	> 50	Yes	Yes
	Pro	BC-PRO	100	Yes	> 50	Yes	Yes
	Master	BC-MAS	300	Yes	> 50	Yes	Yes

## Activate Your Software

Activate Software with Proof of Purchase at [security.bioconnect.com/software-activation/](http://security.bioconnect.com/software-activation/)

[bioconnect.com/support](http://bioconnect.com/support)  
[sales@bioconnect.com](mailto:sales@bioconnect.com)  
 1-855-368-3743